

DBH (Diameter at	Minimum Protection	
Breast Height)	Zone (TPZ) Distance	
Trunk Diameter (cm)	Required (m)	
less than 10 10 - 29 30 - 40 41 - 50 51 - 60 61 - 70 71 - 80 81 - 90 91 - 100 > 100	1.2 1.8 2.4 3.0 3.6 4.2 4.8 5.4 6.0	

measurement of DBH taken at 1.4m above grade

TPZ distances measured from outside edge of trunk flare

T-BARS, 2400mm LENGTH, SPACED SURFACE ROOTS. T-BARS SECURED FENCE WITH #10 GALVANIZED WIRE AT THREE EVENLY SPACED LOCATIONS ALONG LENGTH OF T-BAR. T-BARS TO BE INSTALLED AT MINIMUM 1200mm DEPTH BELOW GRADE, TYPICAL ENTIRE LENGTH OF PROTECTIVE FENCING.

PROTECTIVE FENCING FOR WOOD LOTS OR GROUPS OF TREES TO BE POSITIONED AT A MINIMUM DISTANCE OF 1000mm BEYOND THE DRIP LINE OF EACH WOOD LOT OR GROUP OF TREES TO BE PRESERVED, OR AS DIRECTED BY THE CONSULTING ARBORIST.

## NOTES:

- ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED
- ALL PROTECTIVE FENCING TO BE LOCATED AS DIRECTED BY I.S.A CERTIFIED ARBORIST
- TPZ FENCING SHALL NOT BE ATTACHED TO TREES
- ALL TREE PROTECTION SHALL BE IN PLACE AND MUST BE INSPECTED AND APPROVED BY THE TOWN PRIOR TO ANY CONSTRUCTION ACTIVITIES, AND REMAIN IN PLACE UNTIL ALL CONSTRUCTION ACTIVITIES HAVE CONCLUDED, OR AS DIRECTED BY THE CONSULTING ARBORIST
- NO CONSTRUCTION ACTIVITY, MATERIAL STORAGE, GRADE CHANGES, SURFACE TREATMENT OR EXCAVATIONS OF ANY KIND IS PERMITTED WITHIN THE TREE PROTECTION ZONE
- REFER TO TREE INVENTORY & PRESERVATION PLAN FOR REQUIRED FENCING TYPE
- 7. REFER TO TOWN OF WHITBY STANDARD #702 FOR GENERAL TREE PROTECTION NOTES

## THE CORPORATION OF THE TOWN OF WHITBY

## PLANNING & DEVELOPMENT DEPARTMENT

CHECKED	lus:	
APPROVED	×	
SCALE:	N.T.S	

## LIGHT DUTY TREE PRESERVATION **FENCE**

DWG. DATE: JANUARY 2021	
REVISION No.: 002	
REVISION DATE: MAY. 2022	
DWG No. 700	